FOUND 5/8" REBAR WITH ALUMINUM CAP AND BEARING TREES AT SECTION CORNER FOUND 1/2 REBAR N 79°19'15" W 91.27' FROM CORNER FOUND 5/8" REBAR WITH PLASTIC CAP AT QUARTER CORNER SEC 34 *∏SEC* 35 N 89°58'43" E 2629.57' SEC 3 SEC 2 SEC 2 SEC 11 FOUND ORIGINAL MARKED STONE
AT QUARTER CORNER—SET 5/8"
REBAR WITH DUCHESNE COUNTY
ALUMINUM CAP AT CORNER WITH
STONE RESET ALONGSIDE N 89°07'50" W 5279.67' 2644.57' 2635.09' FOUND ORIGINAL MARKED STONE AND BEARING TREE AT QUARTER CORNER—SET DUCHESNE COUNTY 1322.29' ALUMINUM CAP ON 5/8" REBAR AT CORNER WITH STONE RESET UPSIDE DOWN ALONGSIDE S 89°07'04" E 2646.80' 1323.40' W%S%N%N%SW% 10.033 Acres S 89.06'18" E 2649.03' 1324.51 S 89'04'46" E 1326.74' FOUND ORIGINAL MARKED STONE AT SECTION CORNER FOUND DUCHESNE COUNTY ALUMINUM CAP S 89°01'44" E 2662.39' SEC 3 SEC 2 AT QUARTER CORNER 1331.19 N 89°01'47" W 2662.40' SEC 2 SEC 1 SEC 11 SEC 12 S 89°01'47" E 2015.04' FOUND ORIGINAL NOTCHED STONE AND BEARING TREES AT SECTION CORNER


RECORD OF SURVEY FOR

EDWARD TOMANENG

SECTION 2, TOWNSHIP 4 SOUTH, RANGE 8 WEST UINTAH SPECIAL BASE AND MERIDIAN

PROPERTY DESCRIPTION BY SURVEY

The W_{2} of the S_{2} of the N_{2} of the N_{2} of the SW4 of Section 2, Township 4 South, Range 8 West of the Uintah Special Base and Meridian, containing 10.033 acres.



LEGEND

FOUND SECTION CORNERS AS NOTED ON PLAT

FOUND OR REESTABLISHED QUARTER CORNERS AS NOTED

- ▲ FOUND "T" POST USED TO DETERMINE PROPERTY LINES
- FOUND REBAR SET BY OTHERS
- SET LATH ON PROPERTY LINE
- 5/8"X24" REBAR WITH CAP STAMPED ALLRED SURVEYING
 SET BY THIS SURVEY.
- * * * EXISTING FENCES
- ----- CHRISTENSEN LINES

NARRATIVE AND NOTES

THIS SURVEY WAS PERFORMED AT THE REQUEST OF ED TOMANENG THE PURPOSE OF DETERMINING THE LOCATION OF THE PROPERTY CORNERS OF THE SHOWN PARCEL.

BASIS OF BEARINGS

THIS SURVEY WAS PERFORMED USING GLOBAL POSITIONING SYSTEM (G.P.S.) EQUIPMENT AND PROCEDURES USING THE UTAH G.P.S. VIRTUAL REFERENCE STATION CONTROL NETWORK MAINTAINED AND OPERATED BY THE AUTOMATED GEOGRAPHIC REFERENCE CENTER. THE BASIS OF BEARINGS IS GEODETIC NORTH DERIVED FROM G.P.S. OBSERVATIONS AT A CONTROL POINT THE SECTION CORNER COMMON TO SECTIONS 15, 16, 21, AND 22, T2S, R1W, U.S.B.&M. LOCATED AT LAT: 40°08'48.66219" N & LONG: 110°44'01.97379" W USING SAID CONTROL NETWORK.

SURVEYOR'S CERTIFICATE

I, Jerry D. Allred, do hereby certify that I am a Professional Land Surveyor, and that I hold certificate no. 148951 as prescribed by the laws of the State of Utah: I further certify that this plat and its computations were prepared from the field notes and electronic data collector files of an actual survey made by me, or under my personal supervision, of the parcels of land shown hereon, and that the monuments indicated were found or set during said survey, and that this plat accurately represents said survey to the best of my knowledge.

No. 148951 JERRY D. ALLRED 26 DEC 18

JERRY D. ALLRED, PROFESSIONAL LAND SURVEYOR CERTIFICATE NO. 148951 (UTAH)

JERRY D. ALLRED & ASSOCIATES, INC.

26 DEC 2018 18-100-100 2 OF 3

RRY D. ALLRED & ASSOCIATES, IN
SURVEYING CONSULTANTS

1235 NORTH 700 EAST——P.O. BOX 975
DUCHESNE, UTAH 84021
(435) 738—5352